




AIR HOSES

Fast Stats



POLYURETHANE



PREMIUM RUBBER



RED RUBBER



PVC

Operating Pressure	200 PSI	300 PSI	300 PSI	300 PSI
Burst Strength	800 PSI	1200 PSI	900 PSI	1200 PSI
Cold Weather Flexibility	Best	Best	Good	Fair
Temperature Range	-40° - 150° F	-40° - 212° F	-20° - 165° F	0° - 150° F
Field Repairable	Yes	Yes	No	No
Swivel Fittings	Yes	No	No	No
Oil Resistant	Yes	No	Yes	Yes
Abrasion Resistant	No	Yes	Yes	Yes
Origin	Taiwan	USA	Taiwan	Taiwan
Color	Blue	Gray	Red	Red
Available Sizes:				
1/4" Diameter	25', 50', 100', 328' Lengths	25', 50', 100', 750' Lengths	25', 50', 100' Lengths	25', 50', 100' Lengths
3/8" Diameter	25', 50', 100', 328' Lengths	25', 50', 100', 750' Lengths	25', 50', 100' Lengths	25', 50', 100' Lengths

1 Year Warranty on All Hoses

Grip-Rite® air hoses are distributed by PrimeSource Building Products, Inc.

PRIME SOURCE
BUILDING PRODUCTS, INC.
Irving, Texas 75038 USA

800-676-7777
www.grip-rite.com
www.primesourcebp.com
© 2011 PrimeSource Building Products, Inc.

GRHSSTATS
04/2011