



# PAINTERS CAULK

DOORS | WINDOWS | SIDING | TRIM | MOULDING | BASEBOARDS | VENTS

Grip-Rite® Painters Caulk is a general purpose siliconized acrylic sealant for interior and exterior use. It is easy to use, dries quickly and cleans up with water. It offers a water-resistant seal once cured, tools easily, great weather resistance and can be painted with a water-based paint. It bonds well to wood, metal, glass, tile, drywall, plaster, concrete, plastic, fiberglass, masonry, aluminum, brick and most common building materials.



## Features & Benefits

- Repair, seal & fill
- Fills gaps up to 1" wide
- UV-resistant
- Mold and mildew resistant
- VOC-compliant
- Can be painted with water-based paints one hour after application
- Compatible with most common building materials

## Use on

Doors, windows, siding, trim, moulding, baseboards and vents.

## Adheres to

Glass/tile, wood, metal, drywall/plaster, masonry/brick/concrete, plastic, and fiberglass.

## Physical and Chemical Characteristics

- **Type:** Siliconized acrylic
- **VOC:** <50 g/L (<1.5%)
- **Working time:** 10-15 minutes
- **Full cure:** 24 hours for 1/4" bead
- **Application temperature:** 40°F-120°F
- **Service temperature:** 0°F-160°F
- **Storage life:** 24 months in tightly closed containers below 80°F
- **Coverage:** 51 linear feet at a 3/16" bead
- **Cleanup:** Water when wet. Mineral spirits when dried. Follow solvent vendor's precautions.
- **Paintable:** Yes, after 1 hour



# PAINTERS CAULK

DOORS | WINDOWS | SIDING | TRIM | MOULDING | BASEBOARDS | VENTS

## Specifications

Meets ASTM C-834 Type OP, Grade -18°C.

## User Tips

Do not apply on exterior surfaces if rain is expected within 24 hours. Not designed for continuous submersion or use below the waterline. Dry time may be extended in humid or cold conditions. If joint depth exceeds 1/4", use backing material. For best results, store above 40°F.

## Instructions for Use

1. Remove dirt and grease.
2. If joint exceeds 1/2" x 1/2", use backer rod.
3. Cut nozzle to desired bead size.
4. Load cartridge into caulking gun.
5. Place nozzle into joint and apply sealant into gap. Apply above 40°F.
6. Smooth bead within 3-5 minutes.
7. Protect from moisture for at least 24 hours for proper cure.
8. Store unused sealant in dry area above freezing. Not intended for underwater use, food contact surfaces, areas of continuous submersion or where FDA compliance is necessary.

## 10 Year Limited Warranty

PrimeSource® warrants this product will meet PrimeSource's® specifications if properly stored and applied. If not satisfied, return proof of purchase for refund. PrimeSource® shall not be liable for damages in excess of the purchase price. This is the sole and exclusive remedy/liability for product defects/failure. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS. You may also have other rights that vary from state to state, so the above limitations/exclusions may not apply to you.



GRIP-RITE® CAULKS AND ADHESIVES ARE EXCLUSIVELY DISTRIBUTED BY  
PRIME SOURCE BUILDING PRODUCTS, INC.

# Grip Rite

## PAINTERS PLUS CAULK

TECHNICAL DATA SHEET

DOORS | WINDOWS | SIDING | TRIM | MOULDING | BASEBOARDS | VENTS

Grip-Rite® Painters Plus Caulk is a premium grade, general purpose, siliconized acrylic sealant for interior and exterior use. It is easy to use, dries quickly and cleans up with water. It bonds well to wood, metal, glass, tile, drywall, plaster, concrete, plastic, fiberglass, masonry, aluminum, brick and most common building materials. It offers a water-resistant seal once cured, tools easily, has great weather resistance and can be painted with a water-based paint.



### Features & Benefits

- Fills gaps, seals joints and repairs cracks
- Dries quickly and tools easily
- Fills gaps up to 1" wide
- Mold and mildew resistant
- VOC-compliant
- Can be painted with water-based paints one hour after application
- Compatible with most common building materials

### Use on

Doors, windows, siding, trim, moulding, baseboards and vents.

### Adheres to

Glass/tile, wood, metal, drywall/plaster, masonry/brick/concrete, plastic and fiberglass.

### Physical and Chemical Characteristics

- **Type:** Siliconized acrylic
- **VOC:** <50 g/L (<1.5%)
- **Working time:** 10-15 minutes
- **Full cure:** 24 hours for 1/4" bead
- **Application temperature:** 40°F-120°F
- **Service temperature:** 0°F-160°F
- **Storage life:** 24 months in tightly closed containers below 80°F
- **Coverage:** 51 linear feet at a 3/16" bead
- **Cleanup:** Water when wet. Mineral spirits when dried. Follow solvent vendor's precautions.
- **Paintable:** Yes, after 1 hour

The logo for Grip Rite, featuring the words "Grip" and "Rite" stacked vertically in a bold, white, sans-serif font. The text is set against a red, rounded rectangular background that has a slight 3D effect with a dark red shadow on the right side.

®

TECHNICAL DATA SHEET

# ***PAINTERS PLUS CAULK***

DOORS | WINDOWS | SIDING | TRIM | MOULDING | BASEBOARDS | VENTS

## **Specifications**

Meets ASTM C-834 Type OP, Grade -18°C.

## **User Tips**

Do not apply on exterior surfaces if rain is expected within 24 hours. Not designed for continuous submersion or use below the waterline. Dry time may be extended in humid or cold conditions. If joint depth exceeds 1/4", use backing material. For best results, store above 40°F.

## **Instructions for Use**

1. Remove dirt and grease.
2. If joint exceeds 1/2" x 1/2", use backer rod.
3. Cut nozzle to desired bead size.
4. Load cartridge into caulking gun.
5. Place nozzle into joint and apply sealant into gap. Apply above 40°F.
6. Smooth bead within 3-5 minutes.
7. Protect from moisture for at least 24 hours for proper cure.
8. Store unused sealant in dry area above freezing. Not intended for underwater use, food contact surfaces, areas of continuous submersion or where FDA compliance is necessary.

## **40 Year Limited Warranty**

PrimeSource® warrants this product will meet PrimeSource's® specifications if properly stored and applied. If not satisfied, return proof of purchase for refund. PrimeSource® shall not be liable for damages in excess of the purchase price. This is the sole and exclusive remedy/liability for product defects/failure. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS. You may also have other rights that vary from state to state, so the above limitations/exclusions may not apply to you.

**PRIMESOURCE**  
BUILDING PRODUCTS, INC.

GRIP-RITE® CAULKS AND ADHESIVES ARE EXCLUSIVELY DISTRIBUTED BY  
PRIMESOURCE BUILDING PRODUCTS, INC.