



FAST STATS

Pneumatic Tools

				
	GRTFR83 Framing	GRTFC83 Framing	GRTCN90 Framing	GR150 Framing/Specialty
FIRING MODE	Selectable Trigger, Bump or Sequential	Selectable Trigger, Bump or Sequential	Selectable Trigger, Bump or Sequential	Push
MAGAZINE CAPACITY	75 Nails	80 Nails	200-300 Nails	30 Nails
OPERATING PRESSURE	70-120 PSI	70-120 PSI	80-120 PSI	100-120 PSI
FASTENER TYPE	21° Plastic Strip Round Head Framing Nails 	30°-34° Offset Round & Clipped Head Paper Tape Framing Nails 	15° Wire & Plastic Sheet Coil Nails 	30°-34° Paper Tape & Plastic Strip Metal Connector Nails 
FASTENER RANGE	Length: 2" to 3-1/4" Diameter: .113" to .148"	Length: 2" to 3-1/4" Diameter: .113" to .131"	Length: 1-3/4" to 3-1/2" (Wire) 1-3/4" to 3" (Plastic) Diameter: .099" to .148"	Length: 1-1/2" Diameter: .131" to .148"
WEIGHT	6.9 lb.	7.3 lb.	6.6 lb.	4.4 lb.

				
	GRSB250 Framing/Specialty	GRSB150 Framing/Specialty	GRTMP16 Framing/Specialty	GRTRN45 Roofing
FIRING MODE	Sequential	Sequential	Push (multi-blow)	Bump Fire
MAGAZINE CAPACITY	33 Nails	33 Nails	N/A	120 Nails
OPERATING PRESSURE	80-120 PSI	80-120 PSI	80-110 PSI	70-120 PSI
FASTENER TYPE	30°-34° Paper Tape Metal Connector Nails 	30°-34° Paper Tape Metal Connector Nails 	Hand Driven Nails 	15° Coil Roofing Nails 
FASTENER RANGE	Length: 1-1/2" to 2-1/2" Diameter: .131" to .162"	Length: 1-1/2" Diameter: .131" to .148"	Most nails up to 16d (3-1/2")	Length: 7/8" to 1-3/4"
WEIGHT	5.7 lb.	4.4 lb.	1.1 lb.	5.04 lb.

FAST STATS

Pneumatic Tools



GRC58A Roofing/House-Wrap



GRTCS250 Siding/Fencing



GRTCS250Z Siding/Fencing



GRTSM2016C Stapler

FIRING MODE	Bump Fire	Selectable Trigger, Bump or Sequential	Selectable Trigger, Bump or Sequential	Bump Fire
MAGAZINE CAPACITY	110 Caps & Staples	200-350 Nails	300 Nails	140 Staples
OPERATING PRESSURE	100-120 PSI	70-120 PSI	80-120 PSI	70-120 PSI
FASTENER TYPE	80 series staples & 1" plastic caps 	15° Wire & Plastic Sheet Coil Nails  	0° Plastic Sheet Coil Nails 	16 Gauge 7/16" Crown Staples 
FASTENER RANGE	Staples: 5/32" to 5/8" Caps: 1" diameter	Length: Wire 1-3/4" to 2-1/2" Plastic 1-1/4" to 2-1/2" Diameter: .090" to .099"	Length: 1-1/4" to 2-1/2" Diameter: .083" to .113"	1" to 2" leg
WEIGHT	4.0 lb.	4.8 lb.	4.1 lb.	4.20 lb.



GRTSN150 Staplers



GRTFN250 Finish



GRTBN200N Finish

FIRING MODE	Selectable Trigger, Bump or Sequential	Selectable Trigger, Bump or Sequential	Selectable Trigger, Bump or Sequential
MAGAZINE CAPACITY	140 Staples	110 Nails	110 Nails
OPERATING PRESSURE	70-110 PSI	70-110 PSI	70-110 PSI
FASTENER TYPE	18 Gauge 1/4" Crown Staples 	16 Gauge Finish Nails 	18 Gauge Brad Nails 
FASTENER RANGE	3/4" to 1-1/2" leg	1" to 2-1/2"	5/8" to 2"
WEIGHT	2.8 lb.	3.9 lb.	2.9 lb.



7 YEAR LIMITED WARRANTY ON ALL TOOLS
90 DAY SATISFACTION GUARANTEE ON ALL TOOLS

Exclusively distributed by
PRIME SOURCE
GLOBAL REACH. HOMETOWN SERVICE.™



800-676-7777
www.grip-rite.com

WE BUILD AMERICA™