

ProWrap™ BUTYL and ProWrap™ FLEX

Window and Door Protector Tape



ProWrap™ Butyl and ProWrap™ Flex Window and Door Protector Tape – Your Ultimate Defense Against the Elements! Guard your windows and doors with the power of Grip-Rite®. Our protector tape provides a durable shield against rain, wind, and extreme weather conditions, ensuring your home remains a fortress against the elements.



PRIMER-LESS



**RESISTS STRONG
WINDS & GUSTS**



**REDUCES DRAFTS &
WATER LEAKS**

RECOMMENDED USES

Use ProWrap™ to waterproof wood, brick, concrete, and metal surfaces to ensure a continuous air/vapor barrier on the following structures:

- Doors
- Windows
- Joists between waterproofing membranes installed without overlaps

PRODUCT ADVANTAGES

- Primer-less Application
- Can be installed as part of a continuous air barrier
- Meets stringent industry standards
- Resists strong winds and gusts
- Reduces drafts and water leaks
- Sealant stays flexible at low temperatures
- Conformable and UV stable
- Easy release split back liner for simplified installation



View Additional Information



ProWrap™ BUTYL

ProWrap™ FLEX



ProWrap™ BUTYL

Grip-Rite® BUTYL Window & Door Protector is a primer-less self-adhesive membrane that can reduce drafts and water leaks. Use it with all Grip-Rite® water-resistive barriers to provide a simplified flashing solution for doors, windows and other protrusions.

STORAGE:

Protector from exposure to direct sunlight during storage. It is recommended to be stored inside or under cover below 90-degrees Fahrenheit.

ProWrap™ FLEX

Grip-Rite® FLEX Window & Door Protector is an extensible and primerless self-adhesive membrane for detailing windowsills and other radial surfaces. Use it with all Grip-Rite® water-resistive barriers and Grip-Rite® ProWrap™ BUTYL for an integrated flashing system.

PRECAUTIONS:

Protect from high heat or other ignition sources during shipment, storage and application.

Properties, Standards and Products

PROWRAP™ BUTYL (JSC ITEM GRADE: WSA-04)

PROPERTY	STANDARD	UNITS OF MEASURE	TYPICAL VALUE
Facer Color	Internal	--	White
Minimum Application Temperature	Internal	Degrees Fahrenheit	20
Elevated Temperature Exposure	AAMA 711-13	Level	Level 3 (176°F)
Tensile Strength (MD)	ASTM D-882-95A	psi	2,349
Elongation at Break (MD)	ASTM D-882-95A	%	893
Nail Sealability	AAMA 711-13	Pass/Fail	Pass
Cold Temperature Pliability	AAMA 711-13	Pass/Fail	Pass
Maximum Outdoor Exposure	Internal	Months	6
Peel Adhesion - Stainless Steel	ASTM D 3330	lbs/inch	6.4

SKU	SIZE	COLOR	WEIGHT/ROLL	CARTON QTY	WEIGHT/CARTON	PAL QTY
GRWRWD4BT	4" x 75'	white/red	1.6	9	14.5	522
GRWRWD6BT	6" x 75'	white/red	2.5	6	15	348
GRWRWD9BT	9" x 75'	white/red	3.5	3	10.5	222
GRWRWD12BT	12" x 75'	white/red	4.5	3	13.5	174

PROWRAP™ FLEX (JSC ITEM GRADE: WSA-F-04)

PROPERTY	STANDARD	UNITS OF MEASURE	TYPICAL VALUE
Facer Color	Internal	--	White
Minimum Application Temperature	Internal	Degrees Fahrenheit	20
Elevated Temperature Exposure	AAMA 711-13	Level	Level 3 (176°F)
Tensile Strength (MD)	ASTM D-882-95A	psi	1288
Nail Sealability	AAMA 711-13	Pass/Fail	Pass
Cold Temperature Pliability	AAMA 711-13	Pass/Fail	Pass
Maximum Outdoor Exposure	Internal	Months	6
Peel Adhesion - Stainless Steel	ASTM D 3330	lbs/inch	2.5

SKU	SIZE	COLOR	WEIGHT/ROLL	CARTON QTY	WEIGHT/CARTON	PAL QTY
GRWRWD6FLX	6" x 50'	white/red	6	6	6	180
GRWRWD9FLX	9" x 50'	white/red	8	3	8	120

For installation instructions and more information, visit grip-rite.com.

PRIME**SOURCE**
BUILDING PRODUCTS, INC.

A PrimeSource® Brands Company



Contact your PrimeSource® Building Products representative to order today.

800-676-7777 | primesourcebp.com

Grip-Rite® Flashing Tape is exclusively distributed by PrimeSource® Building Products, Inc. 1321 Greenway Drive, Irving, TX 75038-2504. Visit grip-rite.com or call 800-676-7777 for details, warranty information and limitations. Pricing and availability are subject to change without notice. © 2024 PrimeSource® Building Products, Inc. All Rights Reserved.

PSBPGRPWBFTS0324